

KNSR elbow 180/UNI-CZ2 (ML) 4seg



**Product code:** Z7DAR-KNSR180/UNI  
**Brand:** Array  
**Category:** Flues and chimneys > Chimneys for fireplaces and stoves

**PRICE : €51.90**

About the product

**Manufacturer:**  
**Country of origin:**  
**Height, mm:** 515  
**Width, mm:** 180  
**Depth, mm:** 180  
**Made of:**  
**Color:**  
**Chimney diameter, mm:**  
**Wall thickness, mm:** 2  
**Item type:**  
**Warranty, year:** 2  
**Max. temperature, C:** 600

Description

Chimney connection system is used for building chimney connections (connecting stove with chimney duct), it is made with mild steel sheet type DC01 (in thickness 2,0 mm). It is recommended as a smoke extraction duct from solid fuels burning devices, where the temperature can rise up to 1000°C. Maximal temperature of constant work: 600°C. Pipe elements are welded with laser technology, that guarantees highest connection quality, aesthetics and tightness.

- Advantages:**
- easy and simple mounting process;
  - possibility of applying as a connectors to stoves fired with wide spectrum of solid fuels;
  - can not work as a chimney duct

**Usage:**  
for building chimney connections (connecting stove with chimney duct)